



## Line Textured Mineral Plaster (White)

### Product Description

Cement-based, line-textured, decorative exterior cladding prepared for composite thermal insulation systems.  
(according to TS EN 13499:2006 standard)

### Areas of Use

- As a last layer decorative coating material in jacketing systems,
- It is used on interior and exterior plasters.

### Application Surfaces Exteriors;

- Cement based plasters,
- Gas concrete (applied gas concrete plaster),
- Please consult us for other surfaces.

### Advantages

- It is easy to apply and provides excellent adhesion.
- It is decorative and provides a homogeneous application.
- The wavy appearance in thermal insulation systems applications can be corrected.
- It is resistant to water and frost.
- It is resistant to external influences and protects the structure for many years.
- It allows the structure to breathe by allowing the diffusion of water vapor.
- Exterior paint can be applied on it.

### Preparation of the Surface

- The application surface and boards should be strong and be cleaned from anti-adhesion agents such as dust, oil, paint, silicone, curing agent, detergent.
- Before application, Newsan Multi Coating Primer is applied on the surface by brush or roller.
- Before application, the surface must be



moistened and saturated with water in very hot and windy weather.

### Preparation of Mortar

- 25 kg. Newkim Decorative Plaster is added to approximately 6-7 liters of clean water and preferably mixed with a low speed mixer or trowel so that no lumps remain.
- The prepared mortar is rested for 2-3 minutes to mature and used again by mixing.
- The mixture in the bowl should be consumed within 1.5-2 hours.

### Application Details

- The material should be applied to the surface with a steel trowel and spread over the entire surface of equal thickness.
- Application thickness should be adjusted according to the largest aggregate.
- Within 10 minutes at the latest, add a pattern to the plaster by making horizontal or vertical movements with a plastic trowel while the material is still wet.
- If the air temperature is high after the application is completed, moisten the surface until cemented.

### Product Details

Line textured (Horizontal or Vertical)

### Application Limit

- It is not applied on horizontal and inclined surfaces below 45 degrees.
- It is not applied directly on brick, briquette and gas concrete and on poorly plastered surfaces

### Application Requirements

- The ambient temperature should be between +5 °C and +35 °C.
- Avoid application in very humid and / or very hot weather, under strong wind or sun.
- It should not be applied on surfaces that are frozen, melting or that are in danger of frost within 24 hours.

### Application Tools

- Steel trowel, plastic trowel.

### Warnings & Suggestions

- While preparing the mortar, the recommended water ratio, mixing and resting times must be observed.
- Previously prepared slightly hardened materials should not be included in the new mixture.
- Application under direct sun should be avoided.
- After drying, the surface should be painted with silicone-added exterior paint.
- Dark colors should not be preferred for applications on exterior thermal insulation systems.
- The bright reference value of the color to be selected must be greater than 25.
- Dark colors can only be used as decorative if they do not cover more than 10% of the facade.
- After application, all tools used should be washed with water before drying.
- It should be waited at least 7 days before starting the paint application.

### Technical Information

Technical Information is relative to 55% ( $\pm 5$  °C) relative humidity environment at 23 °C ( $\pm 2$  °C).

|                         |                               |
|-------------------------|-------------------------------|
| Appearance              | White-colored granules        |
| Powder Density          | 1.55 kg. / Lt. ( $\pm 0.1$ )  |
| Water Mixture           | 6-7 Lt. water / 25 kg. Powder |
| Ratio Rest Time         | 2-3 minutes                   |
| Pot Life                | Approximately 1.5-2 hours     |
| Application Temperature | +5°C / +35°C                  |
| Application Thickness   | 2 mm / min.                   |
| Adhesion Strengt        | >0.8 N/mm <sup>2</sup>        |



#### Consumption

3 kg / m<sup>2</sup>



#### Packaging

25 kg. Kraft Bag



#### Shelf Life

1 year from the date of production  
in drought and dry environments



#### Color

White