



## Non-Stop Solution

### Product Description

It is produced as a transparent solution that provides non-slip properties on shiny and slippery ceramic-tile surfaces and increases the friction coefficient of the surface.

### Advantages

- It provides anti-slip effect by penetrating into the floor without changing the appearance of the tiles and ceramics on which it is applied.
- It shows anti-slip performance in both wet and dry conditions.

### Areas of Use

- It has a wide range of applications, including floors with low friction coefficient, ceramic and tiled floors, poolsides, kitchens, dining halls, bathrooms, balconies, terraces and stair steps, in accordance with occupational safety rules.
- Can be used indoors and outdoors.

### Application

- The ceramic and tile floor on which the application will be applied should be cleaned of dust and dirt, washed and rinsed with plenty of water.
- After obtaining a dry surface after cleaning, the anti-slip solution should be poured onto the surface and rubbed thoroughly on the surface with circular movements with a brush.
- During the application, if the floor is checked and it is determined that the desired anti-slip level is reached, the solution should be rinsed from the surface by pouring plenty of water and the application should be terminated.



### Application Time

- Depending on the thickness of the transparent glaze on the surface of the ceramic, it varies between 5 minutes and 45 minutes. After the process is completed, it must be rinsed with plenty of water.

### ATTENTION!

There is a risk of color deformation in dark colored ceramics. For this reason, application should not be made on dark colored ceramics.

It should not remain on the surface for more than 60 minutes.

It should be rinsed with plenty of water.

Do not let the product come into contact with your skin during application.

Use protective gloves and glasses.

Do not breathe the vapor.

### Consumption

100-150 gr/m<sup>2</sup>

### Colour

Transparent

### Storage Conditions

Store in a dry and cool environment, in its original packaging, unopened.

### Packaging

1 lt, 5 lt and 10 lt PE Jerrycan

### Shelf Life

2 years.